

THERMOFORK BBQ THERMOMETER



BBQDF1541

OUR DETAILS SPECIFICATION OF OUR TYPE: BBODF1541, DIGITAL THERMO- FORK AS FOLLOWING:

- 1) POWER: BE REQUIRED 2 "AA" BATTERIES. {1.5V * 2 =3V (DC)}
- 2) TEMPERATURE GUIDE AS FOLLOWING:

VERY RARE	113F -- 120F	45.0C -- 49.5C
RARE	121F -- 129F	49.6C -- 54.5C
MEDIUM	130F -- 138F	54.6C -- 59.5C
MEDIUM WELL	139F -- 148F	59.6C -- 64.5C
WELL	149F -- 173F	64.6C -- 79.0C
PORK / POULTRY	174F -- 212F	79.1C -- 100.0C

- 3) ALARM SYSTEM: WHEN THE TEMPERATURE BE OVER 110C, THE BUZZER WILL BE OPERATED AND BI- BI- VOICE WILL BE ANNOUNCED.
- 4) DATA HOLD FUNCTION: ON/OFF KEY IS PRESSED OVER 1 SECOND. THE DATA HOLD FUNCTION WILL BE USED, AND WITHIN 3 MINUTES TO PRESS THE ON/OFF KEY AGAIN, THE DATA HOLD FUNCTION WILL BE CLEAN OUT.
- 5) AUTOMATICALLY TURN OFF FUNCTION: THERMOS- FORK WILL AUTOMATICALLY POWER OFF IN 3 MINUTES.
- 6) HOW TO USE:
 - A) PRESS THE POWER ON/OFF KEY. PRESS THE FIRST TIME WILL BE POWER ON. AND PRESS THE SECOND TIME WILL BE POWER OFF.
 - B) OPERATER SYSTEM: WHEN PRESS POWER ON, THE "BI-" VOICE WILL BE ANNOUNCED AND ALL OF LED (6 UNITS OF LED) WILL BE INDICATED, IT IS TO CONFIRM THE THERMO- FORK IS WORKING.
 - C) WHEN PRESS POWER OFF, THE THERMO- FORK IS SLEEPING.